


Satcube Ku

"The Satcube Ku terminal exceeds expectations of end users by virtue of its compact size, high bandwidth, flexibility and ease of use."



Steve Slater Managing director, GRC





Lightweight at only 8 kg



Global coverage*



Wi-Fi hotspot or ethernet cable

The Satcube Ku terminal enables users to easily create a reliable Wi-Fi hotspot and get high-speed broadband connection in a minute, empowering communications and execution of critical on-the-spot work assignments.

Its user-interface is highly intuitive, guided by the 3-dimensional "point-and-locate" function to connect to the internet within a minute.

Thanks to its global coverage*, robustness and the possibility to run on batteries, the Satcube Ku enables internet connection in almost any circumstance, making it highly suitable for a wide range of users, such as emergency response, broadcast media, law enforcement, public safety organization, NGOs, telemedecine and more. *With Intelsat's managed service FlexMove



Hot swappable batteries

3 hour transmit time using 3 batteries.



Up to 20mbps

High speed connection.



Fast & intuitive setup

Get connected in a minute

Specifications

Dimensions

8 kg; 470 x 300 x 55 mm 18 lbs; 18.5 x 11.8 x 2.17 inch

Environmental rating

IP65/IP67 water and dust proof

Power

24 VDC, 130 W AC/DC 100 - 240 VAC. 47 - 63 Hz

Antenna parameters

Tx: 13.75 - 14.50 GHz (Ku band) Rx: 10.95 - 12.75 GHz (Ku band) Linear polarisation EIRP: 46 dBW G/T: 9 db/K

Approvals

CE [RED directive (2014/ 53/UE), EN 301 428)] FCC

Internal modem

iDirect IQ 200 Newtech MDM2510 **UHP 210**

Temperature range

-20°C to 50°C/4°F to 122°F

Data rate

Up to 20/20Mbps via HTS

Nellickevägen 22 SE-412 63 Gothenburg, Sweden



Visit satcube.com

info@satcube.com sales@satcube.com +46 (0) 31 701 05 00